

220 West Parkway, Unit 8 - Pompton Plains, NJ 07444 Tel: 973-831-5866 www.globalbd.com

LED 80W Canopy | Model # GBD-80W-CP-80-850-HV-5K



80w |Color 5000 | Lumens 8000 Aluminum | Frosted Lens | Series C

One-piece die-cast aluminum housing. One-piece silicone perimeter lens gasket and closed-cell neoprene housing gasket help to seal out moisture and contaminants. High quality shock proof polycarbonate lens with UV inhibitors.

TECHNICAL SPECIFICATIONS

MODEL:	GBD-80W-CP-80-850-HV-5K
VOLTAGE:	AC100-277V
FREQUENCY:	50/60 Hz
LUMENS EFFICACY:	92.17LM/W
THD:	22%
IP RATING:	IP65
BEAM ANGLE (DEGREE):	110°
POWER:	External
LIFE SPAN (HOURS):	50,000 Hours
LENGTH OF WARRANTY (YEAR	S): 5 Years Standard
MOUNTING:Recess	ed Outlet Box or Ceiling Surface
PERCENTAGE OF WATTAGE SA	VED:>75%

LISTED:DLC, UL, CE,RoHS
POWER FACTOR:
LUMENS: 8000LM
KELVIN (CCT):5,030K
CRI:
WATTAGE:80 W
MATERIALS: Die Cast Aluminum and Bronze Finish
LED CHIPS:Hongli
DIMMING :Yes
PRODUCT LENGTH:315x315x229mm (12.4x12.4x9 in)
WORKING ENVIRONMENT:34°C to 54°C (-30°F to 130°F)















