

220 West Parkway, Unit 8 - Pompton Plains, NJ 07444 Tel: 973-831-5866 www.globalbd.com

2x2 LED 35W Troffer | Model # GBD-JM-TL-22-35-5K



2x2 | 35w |5000 Lumens | White Frame Frosted | LED | Troffer | Series V

Designed to fit any ceiling surface. Builtin for squared/rectangular ceilings with 4" – 5" or less installation depth. Suspended and hanging for other types of ceilings. Environmentally friendly and recyclable. Easy low cost maintenance and repair.

TECHNICAL SPECIFICATIONS

| MODEL: | GBD-JM-TL-22-35-5K |
|----------------------------------|----------------------------------|
| VOLTAGE: | AC100-277V |
| FREQUENCY: | 50/60 Hz |
| LUMENS EFFICACY: | 100 LM/W |
| THD: | 18.89% |
| IP RATING: | IP65 |
| BEAM ANGLE (DEGREE): | 120° |
| POWER: | External |
| LIFE SPAN (HOURS): | 50,000 Hours |
| LENGTH OF WARRANTY (YE | EARS): 5 Years Standard |
| MOUNTING: | Build-in/Suspended/Surface Mount |
| PERCENTAGE OF WATTAGE SAVED:>90% | |
| | |

| LISTED: | ETL,cETLus, FCC, DLC |
|----------------------|---------------------------------|
| POWER FACTOR: | 0.9 |
| LUMENS: | 2000-4000LM |
| KELVIN (CCT): | 5000K |
| CRI: | |
| WATTAGE: | 35 W |
| MATERIALS: | Aluminum Alloy + PC Shell Glass |
| LED CHIPS: | smd 2835 |
| DIMMING : | 0-10V Dimming |
| PRODUCT LENGTH: | 603 x 603 x 78mm |
| WORKING ENVIRONMENT: | 20°C to 50°C (-4°F to 122°F) |















